

TORO

Pro Force®

Turbine debris blower

A FORCE TO BE RECKONED WITH.

The Toro Pro Force debris blower delivers tremendous air power for fast removal of grass clippings, leaves, aeration cores, or other debris from your golf course, sports field and maintained turf areas, as well as paved areas such as golf car paths, park trails or parking lots. Operated by a wireless remote control with unmatched functionality, and with design features such as the durable one-piece plastic nozzle, the Pro Force sets a new standard. Experience the Pro Force debris blower – the better way to get your job done.



Also available: Groundsmaster® 3200/3300
Pro Force front-mount model

toro.com/proforce

FEATURES

- 18.3 kW (24.6 hp) Kohler® Command PRO® engine:
 - Heavy-duty air cleaner
 - Air-cooled
 - Electronically governed
- Efficient turbine-type axial flow fan assembly design
- Wireless remote control
 - Start and stop the engine from the utility vehicle platform for complete operational control
 - 360° nozzle rotation in either direction
 - Adjust engine throttle for power through full RPM range of operation
 - Ergonomic weather-resistant design
- Single-piece impact-resistant plastic nozzle
- Fully enclosed exhaust system
- Rugged construction includes steel trailer frame and sturdy plastic wheel fenders
- Heavy-duty trailer & tow hitch is adjustable in height and length to accommodate different towing utility vehicles
- Warranty: Two-year or 1,500-hour manufacturer's warranty



Chute angle indicator

The Pro Force is a self-contained engine-driven debris blower operated with a handheld wireless RF controller.

It utilises a high-efficiency turbine-type fan assembly designed to deliver greater air power to clear turf or pavement of leaves, grass clippings, twigs, pine needles or other undesirable debris.



PRO FORCE DEBRIS BLOWER*	
MODEL	44552: standard blower 44554: tethered controller
ENGINE	18.3 kW (24.6 hp) Kohler® Command PRO® 725 cc, petrol, 2-cylinder, air-cooled, electronically governed
FUEL CAPACITY	Standard 4.16 gal tank. Optional 8.32 gal tank (part number 130-4371)
FAN DESIGN	High-efficiency, axial flow, turbine-type fan assembly.
CONTROL	Handheld wireless RF controller provides capability to start and stop the engine, adjust engine throttle up and down for high to low RPM range of operation, and rotate nozzle 360° in either direction. Ergonomic, weather resistant. Note: Model 44554 includes tethered controller and is offered in regions where wireless control is not available.
NOZZLE	Single-piece impact-resistant plastic with 33 cm (13") outlet diameter.
ROTOR DIAMETER	35.5 cm (14")
FAN ASSEMBLY DIAMETER	35.5 cm (14")
WEIGHT	215.4 kg (475 lb)
LENGTH	Standard 246 cm (97") from adjustable tow hitch to nozzle outlet. 45.7 cm (18") adjustable length for length range of 200.6–292.1 cm (79–115")
WIDTH	122 cm (48")
HEIGHT	111.7 cm (44")
TOW-BEHIND TRAILER	Lawn-tractor style hitch (Category 1). Three hole locations to accommodate varying receiver heights.
TYRE SIZE	20 x 10-8, 4-ply turf tyre.
FENDERS	Custom injection-moulded plastic.
ACCESSORIES	Optional LED light kit model 44559
WARRANTY	Two-year or 1,500-hour warranty. See operator's manual for details.

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.



The front-mounted Pro Force blower for the Groundsmaster 3200/3300 is driven by the traction unit's implement PTO shaft and is conveniently controlled by the operator from the steering column control pod. Pro Force blowers utilise a high-efficiency turbine-type fan assembly designed to deliver superior air flow to clear turf or pavement of leaves, grass, clippings, twigs, pine needles or other undesirable debris.



PRO FORCE DEBRIS BLOWER ATTACHMENT FOR GROUNDSMASTER 3200/3300, MODEL 31916*	
POWER SUPPLY	Traction unit standard drive shaft
FAN DESIGN	High-efficiency, axial flow, turbine-type fan assembly.
CONTROL	PTO switch on traction unit, blower lift on traction unit, chute control with rocker switch on accessory control pod
NOZZLE	Single-piece impact-resistant plastic with 32.39 cm (12.7") outlet diameter.
ROTOR DIAMETER	35.5 cm (14")
FAN ASSEMBLY DIAMETER	35.5 cm (14")
WEIGHT	197.3 kg (435 lb)
LENGTH	138.4 cm (54.5")
WIDTH	152.4 cm (60") front castor wheel to castor wheel
HEIGHT	133.7 cm (48.7")
GROUND CLEARANCE	24.38 cm (9.6")
TRACTOR MOUNTED	For Groundsmaster 3200/3300 (models 31900, 31901, 31902, 31903)
REQUIRED KITS	Toro auxiliary hydraulic kit 31966 and the Toro control kit 31994. For Groundsmaster 3200 models speed reduction kit (144-3587) is required for optimum performance.
WARRANTY	Two-year or 1,500-hour warranty. See operator's manual for details.

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.



toro.com

Worldwide Headquarters
 The Toro Company
 8111 Lyndale Ave. So.
 Bloomington, MN 55420 USA
 Phone: (1) 952 888 8801

©2024 The Toro Company.
 All Rights Reserved.
 24-244-GB



facebook.com
 twitter.com/TheToroCompany
 youtube.com/ToroCompanyEurope



Count on it.