

# BOWIE

# HYDRO-MULCHER®

## VICTOR 1100

### Specifications for the Bowie Victor 1100

#### Engine:

Yanmar 47 hp Diesel  
Engine

#### Length:

GN 21'-5" (653 cm)  
Trailer 19'-8" (599 cm)  
Skid 13'-10" (422 cm)

#### Width:

GN 7'-5" (226 cm)  
Trailer 7'-5" (226 cm)  
Skid 6'-5" (196 cm)

#### Height:

GN 9'-5" (287 cm)  
Trailer 9'-5" (287 cm)  
Skid 8'-5" (257 cm)

#### Empty Weight:

GN 7250 lbs. (3289 kg)  
Trailer 6755 lbs. (3064 kg)  
Skid 5160 lbs. (2341 kg)

#### Pump Options:

3" Bowie Gear Pump  
4" x 2" Centrifugal Pump

#### Liquid Capacity:

1134 US Gallons (4292 Liters)

#### Optional Equipment:

Clear Water Flush System  
Hose Reel

#### Standard Included

#### Parts and Equipment:

4-Nozzles  
4-Part F Quick Couplers  
1-Part D Quick Coupler  
1-2-5/16" Ball (Trailers)  
Spanner Wrench  
Parts Manual  
Engine Manual  
Warranty



**Bowie's Victor 1100** is available as a trailer, gooseneck or skid model. The **Bowie Victor 1100** is the choice for intermediate hydro-mulching jobs. The gooseneck makes hauling and maneuvering much easier and provides additional area for hauling the product to be sprayed. The skid model can be mounted on your own equipment, and the trailer model can be towed with a standard hitch.

The **Bowie Victor Hydro-Mulchers**® come standard with a shredder box and dual agitators for more production and less loading time. With this size of unit, you can go up to 600 lbs. of mulch per tank load and spray with a hose or from the deck using the ergonomic discharge cannon. The large access opening to the tank allows for easy and quick cleaning. The **Bowie Victor 1100** also features controls on the deck which can be used for ground level operation.

#### For Information / Dealer Location:

[www.bowieindustries.com](http://www.bowieindustries.com)  
1-800-433-0934



[www.bowieindustries.com](http://www.bowieindustries.com)  
PO Box 931  
(800) 433-0934  
Bowie, TX 76230

All specifications subject to change without notice.

## COVERAGE PER TANK LOAD

There is a lot of misinformation and confusion (sometimes intentional) about coverage rates per tank load. Coverage per tank load is a function of the amount of mulch put on the ground. In the event of hydro seeding (seeding not using any mulch), the coverage per tank load is almost limitless. The following is an attempt to shed some light on the situation and give some general information. Please keep in mind that there is no substitute for actual experience.

**Variables:** Type of mulch (virgin wood fiber, paper, blend), brand of mulch, additives making slurry “slicker”, tower operation vs. hose, length of hose if using hose, experience or expertise of operator.

**Generally:** Using a quality brand of virgin wood fiber mulch, without an additive, shooting from the tower, with an average operator, a Bowie Hydro-Mulcher will handle approximately 1 lb. of mulch per 2 gallons of water. The superior mechanical agitation with shredder bar and straight through plumbing system enables these heavier loading rates. The loading rates for paper mulch is approximately 2 lbs. of mulch per 3 gallons of water.

**Basic Math:** Generally, the benchmark rate for mulch application is 2,000 lbs. per acre. Since there are approximately 44,000 sq. ft. per acre, 1 lb. of mulch will cover 22 sq. ft.

**Coverage Per Tank Load Chart:** Using the above assumptions, the following chart gives the approximate coverage per tank load using a 2,000 lbs. per acre rate for virgin wood fiber and paper mulches.

Size	Virgin Wood Fiber	Paper
300	3,300 sq. ft.	4,400 sq. ft.
500	5,500 sq. ft.	7,333 sq. ft.
600	6,600 sq. ft.	8,800 sq. ft.
800	8,800 sq. ft.	11,733 sq. ft.
1100	12,100 sq. ft.	16,133 sq. ft.
1500	16,500 sq. ft.	22,000 sq. ft.
3000	33,000 sq. ft.	44,000 sq. ft.

**Other Mulch Rates:** The above chart is easily converted to other common mulch rates by using the following factors.

- 1,000 lbs. / acre - multiply sq. ft. by 2
- 1,500 lbs. / acre - multiply sq. ft. by 1.33
- 2,000 lbs. / acre - no adjustment necessary
- 2,500 lbs. / acre - multiply sq. ft. by .8
- 3,000 lbs. / acre - multiply sq. ft. by .67

Generally speaking, it requires a higher application of paper mulch to achieve the same results as with virgin fiber mulch. Please consider this when choosing paper vs. virgin wood fiber mulch.