

# BOWIE

# HYDRO-MULCHER®

## VICTOR 800

### **Specifications for the Bowie Victor 800**

#### **Engine:**

Yanmar 47 hp Diesel  
Engine

#### **Length:**

Trailer 18'-2" (554 cm)  
Skid 11'-11" (363 cm)

#### **Width:**

Trailer 7'-5" (226 cm)  
Skid 6'-5" (196 cm)

#### **Height:**

Trailer 9'-5" (287 cm)  
Skid 8'-5" (257 cm)

#### **Empty Weight:**

Trailer 6120 lbs. (2776 kg)  
Skid 4955 lbs. (2248 kg)

#### **Pump Options:**

3" Bowie Gear Pump  
4" x 2" Centrifugal Pump

#### **Liquid Capacity:**

958 US Gallons  
(3626 Liters)

#### **Optional Equipment:**

Clear Water Flush System  
Hose Reel

#### **Standard Included Parts and Equipment:**

4-Nozzles  
4-Part F Quick Couplers  
1-Part D Quick Coupler  
1-2-5/16" Ball (Trailers)  
Spanner Wrench  
Parts Manual  
Engine Manual  
Warranty



**Bowie's Victor 800** is one of our most popular Hydro-Mulchers. The low maintenance, ease of use and high productivity of the **Bowie Victor 800** Hydro-Mulcher® makes it a smart choice. With its many options, this piece of equipment makes it just right for your hydro-mulching needs. The trailer unit features a tandem 8000 lb. torflex axle, electric brakes on both axles, DOT approved LED running lights and an adjustable ball or pintle hitch.

**For Information / Dealer Location:**  
[www.bowieindustries.com](http://www.bowieindustries.com)  
**1-800-433-0934**



All specifications subject to change without notice.

## COVERAGE PER TANK LOAD

There is a lot of misinformation and confusion (sometimes intentional) about coverage rates per tank load. Coverage per tank load is a function of the amount of mulch put on the ground. In the event of hydro seeding (seeding not using any mulch), the coverage per tank load is almost limitless. The following is an attempt to shed some light on the situation and give some general information. Please keep in mind that there is no substitute for actual experience.

**Variables:** Type of mulch (virgin wood fiber, paper, blend), brand of mulch, additives making slurry “slicker”, tower operation vs. hose, length of hose if using hose, experience or expertise of operator.

**Generally:** Using a quality brand of virgin wood fiber mulch, without an additive, shooting from the tower, with an average operator, a Bowie Hydro-Mulcher will handle approximately 1 lb. of mulch per 2 gallons of water. The superior mechanical agitation with shredder bar and straight through plumbing system enables these heavier loading rates. The loading rates for paper mulch is approximately 2 lbs. of mulch per 3 gallons of water.

**Basic Math:** Generally, the benchmark rate for mulch application is 2,000 lbs. per acre. Since there are approximately 44,000 sq. ft. per acre, 1 lb. of mulch will cover 22 sq. ft.

**Coverage Per Tank Load Chart:** Using the above assumptions, the following chart gives the approximate coverage per tank load using a 2,000 lbs. per acre rate for virgin wood fiber and paper mulches.

| Size | Virgin Wood Fiber | Paper          |
|------|-------------------|----------------|
| 300  | 3,300 sq. ft.     | 4,400 sq. ft.  |
| 500  | 5,500 sq. ft.     | 7,333 sq. ft.  |
| 600  | 6,600 sq. ft.     | 8,800 sq. ft.  |
| 800  | 8,800 sq. ft.     | 11,733 sq. ft. |
| 1100 | 12,100 sq. ft.    | 16,133 sq. ft. |
| 1500 | 16,500 sq. ft.    | 22,000 sq. ft. |
| 3000 | 33,000 sq. ft.    | 44,000 sq. ft. |

**Other Mulch Rates:** The above chart is easily converted to other common mulch rates by using the following factors.

- 1,000 lbs. / acre - multiply sq. ft. by 2
- 1,500 lbs. / acre - multiply sq. ft. by 1.33
- 2,000 lbs. / acre - no adjustment necessary
- 2,500 lbs. / acre - multiply sq. ft. by .8
- 3,000 lbs. / acre - multiply sq. ft. by .67

Generally speaking, it requires a higher application of paper mulch to achieve the same results as with virgin fiber mulch. Please consider this when choosing paper vs. virgin wood fiber mulch.