

TORO®

Heavy-Duty Proline 53 cm Walk-Behind Mower (Petrol/Electric)

DESIGNED TO WITHSTAND THE DEMANDS OF PROFESSIONAL GARDENERS AND LANDSCAPERS.

With commercial grade engines, cast aluminium decks, and replaceable steel deck guards, Toro Proline mowers are designed to withstand the demands of professional gardeners and landscapers. Available in petrol or electric, the 53 cm cutting width is just right for medium to large lawns, and a single mechanism lets you quickly adjust the cutting height range from 25 mm to 114 mm. You can quickly set it for your preference of recycling or bagging, and the high-capacity, easy-empty bag saves time. For long-term durability, it features a sealed, maintenance-free transmission and a corrosion-resistant aluminium alloy deck.



toro.com

FEATURES

Performance

- Large 9" x 2", lightweight co-polymer wheels provide a light footprint that is easy on turf
- Recycler® Cutting System—optimised for exceptional mulching and bagging performance
- The large 74 L bag features an easy-empty design, making quick work of clipping disposal
- Cut in more conditions with heights ranging from 2.5 cm to 11.5 cm (1" to 4.5")
- The wide opening and ramped profile of the tunnel maximise bag fill

Petrol Models

- Powered by a Kawasaki FJ180V KAI engine with heavy-duty air filter, spin-on oil filter, and a 3.8 L fuel tank
- Designed for durability, featuring a tubular engine guard, replaceable steel deck wear plates and steel cable routing guards
- Increase productivity with the Blade Brake Clutch (BBC) system that disengages the blades without shutting down engine

Electric Models

- Engine-emission free—Powered by the 60V MAX® Flex-Force Power System®
- Maintenance Free—No air filters or oil changes to worry about
- 10 Ah lithium-ion battery provides 60+ minutes** of run time per battery
- Low hand-arm vibration (0.6 m/s² (2.0 ft/s²)) allows extended daily use

* Battery manufacturer rating = 60V maximum & 54V typical usage. Actual voltage varies with load.
** Based on controlled laboratory testing of product at high speed.

	22275T	22276	22283	22285
POWER SYSTEM				
ENGINE/MOTOR	2.0 kW (2.7 hp) 60 V brushless		Kawasaki® FJ180V KAI, 4-cycle, 179 cc	
STARTER	Push button		Recoil, zone start	Recoil ▶ Blade Brake Clutch
DRIVE SYSTEM	Fixed speed, RWD		Variable speed, rear wheel drive	▶ 3-speed, rear wheel drive
TYRES	23 x 6 cm (9 x 2.5") rubber tyres with poly wheels			
DRIVE TYRES	23 x 6 cm (9 x 2.5") rubber tyres with poly wheels			
BATTERY/FUEL TANK CAPACITY	Battery and charger sold separately	Two 10 Ah lithium-ion batteries, 5.5 A rapid charger, international charge cords included	Petrol/3.8 L (1 gal)	▶ Petrol/3.8 L (1 gal)
SPEED	0–6.0 km/h (0–3.7 mph) forward			
MOWING DECKS				
CUTTING WIDTH	53 cm (21")			
DECK CONSTRUCTION	Recycler/rear bag, corrosion resistant 6 mm (0.24") aluminium			
HEIGHT OF CUT/ADJUSTMENT	25–114 mm (1–4.5"), 4 point			
BLADES	3.4 mm (0.13") thick steel with blade stiffener			
WEIGHT AND MEASUREMENTS				
WEIGHT	46 kg (101 lbs) with battery 43 kg (95 lbs) without battery	47 kg (103 lbs) with battery	50 kg (110 lbs)	56 kg (124 lbs)
BAG CAPACITY	77 L (20 gal)			
HAND-ARM VIBRATION	1.0 m/s ² (3.3 ft/s ²)		2.7 m/s ² (8.9 ft/s ²)	
WARRANTY	2-year warranty for residential ¹ , 1-year warranty commercial		2-year warranty for residential ¹ , 1-year warranty commercial, 3-year warranty for engine ²	

¹ Residential use means use of the product on the same lot as your home. Use at more than one location is considered commercial use and the commercial warranty would apply. Refer to Operator's Manual for further details.

² Some products used on Toro LCE Products are warranted by the engine manufacturer.

▶ Step-up feature

	MODEL	AMPERE-HOUR	WATT-HOUR
FLEX-FORCE POWER SYSTEM® BATTERIES	68810	10.0 Ah	540 Wh
	81875	7.5 Ah	405 Wh

	MODEL	DESCRIPTION
FLEX-FORCE POWER SYSTEM CHARGER	81805	60 V 5.5 A rapid charger

ACCESSORIES
125-1030 Replacement bag; 125-8440 Anti-scalp cup; 130-9701 Steel deck guard; 490-7462 Walk-power mower cover; 130-9734 Rear discharge kit (22283 & 22285); 144-3178 Mulching blade

toro.com

©2024 The Toro Company.
All Rights Reserved.
24-614-GB

Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.

