

TORO

WORKMAN® MDX SERIES

UTILITY VEHICLES



PROVEN COMFORT & PRODUCTIVITY



TORO.COM/WORKMAN

KEY FEATURES

- Total payload up to 1,650 lb. (750 kg).
- Towing capacity up to 1,200 lb. (544 kg) with heavy-duty tow hitch.
- 2WD with front hydraulic disc brakes and rear wheel hydraulic drum brakes.
- 16 mph governed. Optional 20 mph requires ROPS and seat belts.

OPTIMUM COMFORT

The SRQ system boasts an independent A-frame front suspension, a swing-arm rear suspension design with coil-over shock absorbers brought together by the proprietary Active In-Frame twister joint. The result is a smooth ride that you and your team will notice immediately. Designed to reduce fatigue so operators can stay more productive throughout the day.



SUPERIOR RIDE QUALITY (SRQ™)

The Workman MDX series with SRQ combines a coil-over shock absorber suspension design with an Active In-Frame™ twister joint. These features deliver superior ride quality for optimum operator comfort and control. The hefty payload capacity and four-wheel hydraulic brake system enhances productivity to tackle the toughest jobs. The Workman MDX has the power and versatility to help you do more.



RUGGED DESIGN

Virtually unbreakable exterior components make the Workman MDX more durable and dependable. A double-walled composite bed can withstand the elements and heavy loads, and won't rust or dent. This vehicle is built to work as hard as you do, year after year.





TORO.COM/WORKMAN

ROBUST POWER

A 480cc Briggs & Stratton® Vanguard® petrol engine powers the Workman MDX to an impressive 1,250 lb (567 kg) cargo capacity. This vehicle is built to haul your toughest load to any job site.



Visit toro.com or call your local distributor for a full list of available accessories and attachments.

DO MORE.

The Workman MDX series combines comfort and productivity like never before. These utility vehicles have the highest total payload capacities in their class for maximum productivity. Get more jobs done in less time. Whether you are hauling a load or towing equipment, Toro offers a wide selection of attachments and accessories, allowing you to transform your Workman MDX into the right tool for any job or application.



EXCEPTIONAL CONTROL

An automotive-grade rack and pinion steering system delivers exceptional control and lowers steering effort, while operating when loaded or empty. This allows operators to focus on the task at hand and move throughout the property with ease.



ACCESSORY OPTIONS



BRUSH GUARD

Heavyweight front guard helps protect against damage to the body and headlights.



CANOPY

Stay protected from the elements with an extra-wide canopy with rear moisture drainage outlets. Made of durable, high-density polyethylene.




DELUXE HARD CAB

This ROPS and CE-certified cab enclosure features a vented front windscreen for cross ventilation, a glass windscreen and side panels for increased visibility. Doors not included. (Not available on lithium model.)



BEVERAGE CART

Features eight locking dry good doors, two cup dispensers and eight locking cold storage doors. 850+ 12-ounce can capacity and built-in rubbish/recycling bin. Contact Fairway Cafe at golfbeveragecart.com. (Not available on lithium model.)



RECEIVER HITCH

This optional heavy-duty tow hitch increases the towing capacity of the Workman MDX up to 544 kg (1,200 lb).



SIGNAL LIGHT KIT

Headlights are standard. Brake, rear and indicator lights are integrated into one optional kit.



FOLDING WINDSCREEN

Quick and easy fold-down design provides air flow to enhance operator/passenger comfort. Clear high-impact modified acrylic.



SOLID WINDSCREEN

Clear high-impact modified acrylic for protection against the elements.



ELECTRIC BED LIFT

A convenient, easy way to unload the cargo bed. Raises and lowers the bed efficiently within the payload capacity.



LED WORK LIGHTS

Consists of two front-facing and one rear-facing LED work light.



FRONT RECEIVER

Provides optional attachment point for the front of a vehicle equipped with or without the brush guard.

SPECIFICATIONS*

WORKMAN® MDX SERIES		
MODEL	WORKMAN MDX	WORKMAN MDX LITHIUM
POWER SOURCE	480 cc, air-cooled, two-cylinder, Briggs & Stratton® Vanguard®. Meets 2011 EPA and CARB exhaust and evaporative emissions regulations.	HyperCell® lithium-ion batteries with integrated Battery Management System (BMS).
SRQ™ SYSTEM	Active In-Frame™ twister pivot joint, front and rear suspension.	
FRONT SUSPENSION	Modified MacPherson strut, adjustable coil-over shock absorbers.	
REAR SUSPENSION	Trailing arm with adjustable coil-over shock absorbers.	
GROUND SPEED	16 mph, governed. Optional 20 mph requires ROPS and seat belts.	16 mph standard, adjustable from 5–19 mph
BRAKES	Front wheel hydraulic disc. Rear wheel hydraulic drum.	All wheel hydraulic disc brakes. Integrated automatic parking brake.
STEERING	Manual rack and pinion steering system with ergonomically positioned column. Steering wheel has 2.75 turns lock-to-lock with 35 cm (13.75") diameter.	Rack and pinion steering system with ergonomic steering wheel that includes an integrated clip.
FRAME	Welded steel channel and tube in body construction. Frame surfaces are dipped e-coat. Body and bed constructed of dent and corrosion-resistant polyethylene.	Welded steel channel and tube in body construction. Frame surfaces are dipped e-coat and powder coat finished. Body and bed constructed of dent and corrosion-resistant polyethylene.
GROUND CLEARANCE	28 cm (11") at the front with no load or operator, 17 cm (6.5") at the rear with no load or operator.	
TYRES	Front: 22 x 9.5-10, 4-ply. Rear: 24 x 12-10, 4-ply. Optional all-terrain tyres	Front: 22 x 9.5-10, 4-ply. Rear: 24 x 12-10, 4-ply. Mounted on custom aluminium rims.
CHARGER/FUEL CAPACITY	24.6 l	On-board high-efficiency 1,200 W smart charger. AC input voltage 100–240 VAC · AC input frequency 50/60 Hz · Max input current 13.4 A
DIMENSIONS	Width: 155 cm (61"), Length: 307 cm (121"), Wheelbase: 206 cm (81")	
CAB DIMENSIONS INSTALLED	Height: 201.1 cm (79.2"), Width: 162.5 cm (64")	-
CANOPY DIMENSIONS INSTALLED	Height: 201.9 cm (79.5"), Width: 155.4 cm (61.2")	
TURNING CLEARANCE CIRCLE	Inside rear tyre: 221 cm (87"), outside front tyre: 653 cm (257")	
INSTRUMENTATION	Hour meter, low oil pressure warning light, accessory power port. Dash has two cup holders, radio holder and glove box storage.	Hour meter, battery level indicator, USB power port, headlight switch and on/off ignition key switch. Two cup holders, radio holder, in-dash storage compartments, speedometer, gear indicator, estimated charge time and diagnostic/fault codes.
CARGO BED SIZE INTERNAL	Length: 113 cm (44.5"), Width: 125 cm (49"), Height: 26 cm (10.25"), LLDPE resin.	
WARRANTY	Two-year or 1,500-hour warranty. Refer to the Operator's Manual for further details.	Two-year or 1,500-hour warranty. Lithium-ion battery 5 years. Refer to the Operator's Manual for further details

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.

Visit toro.com or call your local distributor for a full list of available accessories and attachments.



WHEN WE SAY **COUNT ON IT**, WE MEAN IT

Every product that carries the Toro® brand is backed by over 100 years of history, innovation and timeless dependability. We never stop investing in research and development to give our customers the latest features. That's why Toro is one of the best-known, most trusted brands in the business. We also stand behind our products with a global network of knowledgeable dealers for parts and service support.

Real people. Real support.
Smart features. Proven dependability.



Count on it.

toro.com
Worldwide Headquarters
The Toro Company
8111 Lyndale Ave. So.
Bloomington, MN 55420, USA
Phone: (1) 952 888 8801
Fax: (1) 952 887 8258

©2024 The Toro Company.
All rights reserved.

24-267-GB

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, design and standard equipment without notice and without incurring obligation. See your distributor for details on all our warranties.



facebook.com/ToroCompany
twitter.com/TheToroCompany
youtube.com/ToroCompanyEurope